



Our Products



Lubricant oils

	viscosity [20 °C]	usage temperature	special features	sealing durability	corrosion protection	EP/AW-add-in
Slip Fluid M-85	85 +/- 15 mPas	-50 bis 120 °C		✓		
Slip Fluid M-1300	1500 +/- 200 mPas	-35 bis 135 °C		✓		
Slip Fluid M-1700	2000 +/- 200 mPas	-35 bis 140 °C		✓		
Slip Fluid	3200 +/- 400 mPas	-30 bis 140 °C		✓		
Slip Fluid FJ.02	7500 +/- 500 mPas	-20 bis 140 °C		✓		
CLP 32	32 +/- 3,2 cSt *	-55 bis 110 °C		✓	✓	✓
CLP 68	68 +/- 6,8 cSt *	-30 bis 130 °C		✓	✓	✓
CLP 220	220 +/- 22 cSt *	-20 bis 140 °C		✓	✓	✓
PMM lub® OD-S1	550 +/- 100 mPas	-20 bis 120 °C	Öl-PTFE-dispersion	✓		
PMM lub® OD-S10	650 +/- 100 mPas	-20 bis 120 °C	Öl-PTFE-dispersion	✓		
PMM lub® OD-S20	2800 +/- 300 mPas	-20 bis 120 °C	Öl-PTFE-dispersion	✓		
PMM lub® OD-E1	8000 +/- 750 mPas	-20 bis 140 °C	Öl-PTFE-dispersion	✓		
PMM lub® OD-E10	11700 +/- 1000 mPas	-20 bis 140 °C	Öl-PTFE-dispersion	✓		

* according to ISO-VG [40 °C]

Our company provides several kinds of individually customized solutions with lubricant greases, pastes and oils. To achieve efficient lubrications we only use high-quality resources for all our products. We consider ourselves as a reliable partner for multi-purpose lubricants in any field of use.

If you need any further information about our products, please feel free to contact us.



PMM-Oil GmbH | August-Rost-Straße 7 | 99310 Arnstadt
 ☎ +49 (0)3628/661199 🌐 www.pmmoil.de ✉ info@pmmoil.de

